

LAB FILTRATION PRODUCTS



Count on RephiLe to filter out your concerns!

RephiQuik Non-sterile Syringe Filters

RephiQuik non-sterile syringe filter is a fast and efficient tool for analytical sample preparation. As a result of high quality polypropylene (PP) housing and low extractable membranes, the filters deliver broad chemical compatibility and excellent performance consistency. The non-sterile filters are available in 13 mm & 32 mm diameters and 4 types of membranes for various application needs, such as HPLC/GC sample preparation or many other applications in pharmaceutical, environmental, biological, food, beverage and agricultural fields.

RephiQuik Non-sterile Filters Specifications

Dimensions	Diameters	13 mm	32 mm
	Effective Filtration Area	0.80 cm ²	4.4 cm ²
	Length, Inlet to outlet	21 mm	26 mm
Housing Materials	Polypropylene(PP)		
Membrane Materials	Hydrophobic PTFE (blue), Nylon (purple), PES (green), Hydrophilic PVDF (yellow)		
Inlet Fittings	Female Luer-Lok		
Outlet Fittings	Male Luer slip		
Process Volume	1-10 mL	10-100 mL	
Hold-up Volume (after air purge)	≤ 15 μL	≤ 80 μL	
Maximum Operating Pressure	10 bar (145 psi)	10 bar (145 psi)	
Maximum Operating Temperature	45 °C		



Order Information

Membrane Type	Out ring Color	Hydrophobicity	Diameter (mm)	Pore Size (μm)	Units/Pk	Catalogue No.
PTFE	Blue	Hydrophobic	13	0.22	100	RJF1322NH
				1000	RJF1322NK	
			32	0.45	100	RJF1345NH
					1000	RJF1345NK
				0.22	100	RJF3222NH
					1000	RJF3222NK
Nylon	Purple	Hydrophilic	13	0.22	100	RJN1322NH
				1000	RJN1322NK	
			32	0.45	100	RJN1345NH
					1000	RJN1345NK
				0.22	100	RJN3222NH
					1000	RJN3222NK
PES	Green	Hydrophilic	13	0.22	100	RJP1322NH
				1000	RJP1322NK	
			32	0.45	100	RJP1345NH
					1000	RJP1345NK
				0.22	100	RJP3222NH
					1000	RJP3222NK
PVDF	Yellow	Hydrophilic	13	0.22	100	RJV1322NH
				1000	RJV1322NK	
			32	0.45	100	RJV1345NH
					1000	RJV1345NK
				0.22	100	RJV3222NH
					1000	RJV3222NK




RephiQuik Max 32 mm Non-sterile Composite Syringe Filters

RephiQuik Max 32 mm non-sterile composite syringe filters provide excellent choices for filtering hard-to-filter high particulate loaded samples up to 100 ml (The volume of sample depends on the characteristic of the sample). They can process two-to-five times more sample volume in less time than conventional filters, significantly enhancing sample preparation efficiency .

Specifications

Dimensions	Diameter	32 mm
	Effective Filtration Area	4.4 cm ²
	Length, Inlet to outlet	26 mm
Housing Material	Polypropylene (PP)	
Membrane Materials	Hydrophilic Nylon (purple), PES (green), Hydrophobic PTFE (blue)	
Pore size of Membrane	0.22µm or 0.45µm	
Inlet Fittings	Female Luer-Lok	
Outlet Fittings	Male Luer slip	
Process Volume	10 - 100 mL	
Hold-up Volume(after air purge)	< 250 µL	
Maximum Operating Pressure	10 bar (145psi)	
Maximum Operating Temperature	45°C	



RephiQuik Max filters contain 3 filtration layers, which reduce blockage and increase volume throughput.

Ordering Information

Membrane Type	Out-ring Color	Hydrophobicity	Units/Pk	Pore Size (µm)	Catalogue No.
PTFE	Blue	Hydrophobic	100	0.22	RJF3P22NH
				0.45	RJF3P45NH
Nylon	Pink	Hydrophilic	100	0.22	RJN3P22NH
				0.45	RJN3P45NH
PES	Green	Hydrophilic	100	0.22	RJP3P22NH
				0.45	RJP3P45NH

Applications

- General filtration of hard-to-filter or viscous samples
- HPLC aqueous sample preparation
- Dissolution testing
- Buffer solutions
- Concentration analysis
- Environmental samples
- Food and beverage
- Biological sample preparation
- Tissue culture media
- Pharmaceutical

RephiQuik 50 mm PTFE Filters

RephiQuik 50 mm PTFE filter is a ready-to-connect filtration unit used in sterilization of fermentor air and the filtration of incubator gas to prevent culture media contamination, as well as sterilization or filtration of an organic solution. It can also be used between a pump and a receiving vessel to protect valves and pump components from damage by aqueous solutions.

Features

- Polypropylene housing and a supported hydrophobic porous PTFE membrane
- Allowing air and gases to pass through freely while blocking aqueous solutions and aerosol contaminants
- Light-weight design fits neatly onto laboratory gas and vacuum lines
- Autoclavable
- 2 package sizes available for supply

Specifications

Diameter		50 mm
Materials of Construction	Housing	Polypropylene (PP)
	Filter Media	PTFE
Inlet/Outlet Connections		1/4" Single Hose Barb
Pore Size		0.22 µm

Ordering Information

Membrane Type	Diameter (mm)	Pore Size (µm)	Units /Pk	Catalogue No.
PTFE	50	0.22	10	RJF502210
			50	RJF502250



RephiDisc Membrane Filters

RephiDisc membrane filters are available in a variety of materials such as MCE, Nylon, PTFE, PES and PVDF. The selected membranes are low in extractables that you don't have to worry about the secondary contamination from the membrane itself for your application. All RephiDisc membranes filters are autoclavable.



Membrane	Pore Size	Diameter (mm)	Units/Pk	Catalogue No.	Pore Size	Diameter (mm)	Units/Pk	Catalogue No.
MCE Hydrophilic	0.22 µm	25	500	RCM2522H5	0.45 µm	25	500	RCM2545H5
		47	100	RCM4722NH		47	100	RCM4745NH
		50	100	RCM5022NH		50	100	RCM5045NH
Nylon Hydrophilic	0.22 µm	25	500	RCN2522H5	0.45 µm	25	500	RCN2545H5
		47	100	RCN4722NH		47	100	RCN4745NH
		50	100	RCN5022NH		50	100	RCN5045NH
PTFE Hydrophobic	0.22 µm	25	500	RCF2522H5	0.45 µm	25	500	RCF2545H5
		47	100	RCF4722NH		47	100	RCF4745NH
		50	100	RCF5022NH		50	100	RCF5045NH
PES Hydrophilic	0.22 µm	25	500	RCP2522H5	0.45 µm	25	500	RCP2545H5
		47	100	RCP4722NH		47	100	RCP4745NH
		50	100	RCP5022NH		50	100	RCP5045NH
PVDF Hydrophilic	0.22 µm	25	500	RCV2522H5	0.45 µm	25	500	RCV2545H5
		47	100	RCV4722NH		47	100	RCV4745NH
		50	100	RCV5022NH		50	100	RCV5045NH

All rights reserved © 2022 RephiLe Bioscience, Ltd.

Labcare Service Ltd.

1A Chapel Hill
Braintree, Essex
CM7 3QT
Tel: + 44 (0)1376-332-909
Email: sales@labcareservice.co.uk
www.labcareservice.co.uk